



optionsforlife[™]
safer for people, pets and planet

section 1 company & product

company: optionsforlife, llc
address: 9 Gold Street, NY, NY 10038
phone: 917-617-9060

emergency phone: 800-535-5053

product chemical family: [Green Seal[™] Certified] polymer blend
(this product is ready-to-use)

product: zinc-free floor seal & finish

section 2 product contents

chemical name, cas no., wt.%, :
water, 7732-18-5, to 47
styrene-acrylic copolymer blend, to 40
non-ionic wax emulsion blend, to 6
diethylene glycol monoethyl-ether, 111-90-0, to 4
styrene-acrylic resin blend, to 3
no zinc and no fragrance

section 3 physical properties

boiling point: approx. 215 degrees F
vapor pressure: not determined
vapor density: 4.85 gm/m³ @ 32 degrees F
% volatile: 78 to 80
completely soluble in water
description: milky colored liquid, acrylic odor
evaporation rate (water=1): <1
specific gravity: 1.03
pH: 8 to 8.5

section 4 fire prevention information

flash point: none
non-flammable
extinguishing media: water or CO2
fire fighting precautions: product is slippery on surfaces
no unusual or explosion hazards

section 5 health hazards and first aid

skin: may cause irritation, dryness or redness, especially to those with skin disorders.
treat by flushing skin with soap and water.
eyes: may cause irritation or tearing.
treat by flushing eye with water for 15 minutes.
nose, throat and lungs: may be irritating to mucous membranes and upper track.
treat by moving to fresh air.
ingestion: if swallowed, do not induce vomiting, drink lots of water and seek medical attention.
exposure limits: not established.
carcinogenicity: no ingredients are listed by the National Toxicology Program (NTP) or the International Agency for Research on Cancer (IARC) as known or possible carcinogens.
Not regulated by OSHA

section 6 protective handling and storage recommendations

keep out of reach of children and pets.
for commercial use by trained persons.
wear protective chemical resistant gloves and eye wear.
keep area ventilated while cleaning.
store container closed, in a cool, but not freezing, place.

section 7 spill or leakage procedures

keep unnecessary personnel away from area.
floors will become slippery, wear slip-resistant boots or shoes.
contain spill and mop/absorb the split liquid.
rinse area with cold water.
dispose material as per local, state and federal laws.

section 8 reactivity information

stable
no hazardous polymerization
no materials to avoid
no hazardous decomposition products known

section 9 shipping information

liquid floor wax
non-hazardous
for a gallon or less: may be shipped as ORM (otherwise regulated material)
larger sizes: ship class number 55

hazardous material identification rating:

health: 1 (on a scale of 0/not hazardous to 4/very hazardous)
flammability: 0
reactivity: 0
personal protection: B

msds number: ofl-fsf-3 date: 01.20.10

material safety data sheet

for occupation safety and health only